

17/25 Versa-Lift with 0 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

0

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Fork Face (mm)	300	5300	5800
600	4300		4700	5200	5600
900	3600		4000	4400	4700
1200	3200		3500	3800	4100
1500	2800		3100	3300	3600
1800	2500		2700	3000	3200

Lift Capacities w/Forks & Boom (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	4900	5500
600	4000		4400	4900	5300
900	3300		3700	4000	4400
1200	2800		3100	3500	3800
1500	2400		2700	3000	3300
1800	2200		2400	2700	2900
2100	1900		2200	2400	2600
2400	1800		2000	2200	2400

Lift Capacities w/Boom Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	5300	5800
600	4200		4700	5100	5600
900	3500		3900	4300	4600
1200	3000		3300	3600	4000
1500	2600		2900	3200	3500
1800	2300		2600	2800	3100
2100	2100		2300	2500	2800
2400	1900		2100	2300	2500

***All Load Capacities are rated with the mast vertical.

17/25 Versa-Lift with 1 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

1

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Fork Face (mm)	300	6100	6800	7400	8100
	600	5000	5500	6100	6600
	900	4200	4700	5100	5600
	1200	3700	4100	4400	4800
	1500	3200	3600	3900	4300
	1800	2900	3200	3500	3800

Lift Capacities w/Forks & Boom (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	5800	6500	7200	7800
	600	4700	5200	5800	6300
	900	3900	4300	4800	5300
	1200	3300	3700	4100	4500
	1500	2900	3200	3600	3900
	1800	2600	2900	3200	3500
	2100	2300	2600	2900	3200
	2400	2100	2300	2600	2900

Lift Capacities w/Boom Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	6100	6800	7500	8200
	600	4900	5500	6000	6600
	900	4100	4600	5000	5500
	1200	3500	3900	4300	4700
	1500	3000	3400	3800	4100
	1800	2700	3000	3300	3700
	2100	2400	2700	3000	3300
	2400	2200	2500	2700	3000

***All Load Capacities are rated with the mast vertical.

17/25 Versa-Lift with 2 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

2

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Fork Face (mm)	300	6900	7700	8500	9200
	600	5700	6300	6900	7600
	900	4800	5300	5900	6400
	1200	4200	4600	5100	5500
	1500	3700	4100	4500	4900
	1800	3300	3600	4000	4400

Lift Capacities w/Forks & Boom (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	6700	7500	8300	9100
	600	5400	6000	6700	7300
	900	4500	5000	5600	6100
	1200	3800	4300	4800	5300
	1500	3300	3800	4200	4600
	1800	3000	3300	3700	4100
	2100	2700	3000	3300	3700
	2400	2400	2700	3000	3300

Lift Capacities w/Boom Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	7000	7800	8600	9400
	600	5600	6300	6900	7600
	900	4700	5200	5800	6300
	1200	4000	4500	5000	5400
	1500	3500	3900	4300	4800
	1800	3100	3500	3900	4200
	2100	2800	3100	3500	3800
	2400	2500	2900	3200	3500

***All Load Capacities are rated with the mast vertical.

17/25 Versa-Lift with 3 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

3

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Fork Face (mm)	300	7800	8700	9600	10500
	600	6400	7100	7800	8600
	900	5400	6000	6600	7200
	1200	4700	5200	5700	6300
	1500	4100	4600	5100	5500
	1800	3700	4100	4500	5000

Lift Capacities w/Forks & Boom (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	7500	8500	9400	10300
	600	6100	6800	7600	8300
	900	5100	5700	6300	7000
	1200	4300	4900	5400	6000
	1500	3800	4300	4800	5200
	1800	3400	3800	4200	4700
	2100	3000	3400	3800	4200
	2400	2800	3100	3500	3800

Lift Capacities w/Boom Only (kgs) and Side Shift					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	7900	8800	9700	10700
	600	6300	7100	7900	8600
	900	5300	5900	6600	7200
	1200	4500	5100	5600	6200
	1500	4000	4400	4900	5400
	1800	3500	4000	4400	4800
	2100	3200	3600	4000	4300
	2400	2900	3200	3600	3900

***All Load Capacities are rated with the mast vertical.