

17/25 Versa-Lift with 0 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

0

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Fork Face (mm)	300	5900	6500
600	4700	5200	5700	6100	
900	4000	4400	4800	5200	
1200	3400	3800	4100	4400	
1500	3000	3300	3600	3900	
1800	2700	2900	3200	3500	

Lift Capacities w/Forks & Boom (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	5500	6100
600	4400	4900	5300	5800	
900	3600	4000	4400	4800	
1200	3000	3400	3700	4100	
1500	2600	2900	3200	3500	
1800	2300	2600	2900	3100	
2100	2100	2300	2600	2800	
2400	1900	2100	2300	2500	

Lift Capacities w/Boom Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	5200	5700
600	4100	4500	4900	5300	
900	3400	3700	4100	4400	
1200	2900	3200	3500	3800	
1500	2500	2700	3000	3300	
1800	2200	2400	2600	2900	
2100	2000	2200	2400	2600	
2400	1800	2000	2200	2300	

***All Load Capacities are rated with the mast vertical.

17/25 Versa-Lift with 1 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

1

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Fork Face (mm)	300	6800	7500
600	5500		6100	6600	7200
900	4600		5100	5600	6000
1200	4000		4400	4800	5200
1500	3500		3800	4200	4600
1800	3100		3400	3700	4100

Lift Capacities w/Forks & Boom (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	6500	7200
600	5100		5700	6300	6900
900	4200		4700	5200	5700
1200	3600		4000	4400	4800
1500	3100		3500	3800	4200
1800	2700		3100	3400	3700
2100	2500		2800	3000	3300
2400	2200		2500	2800	3000

Lift Capacities w/Boom Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	6800	7500
600	5400		6000	6600	7100
900	4400		4900	5400	5900
1200	3800		4200	4600	5000
1500	3300		3600	4000	4400
1800	2900		3200	3500	3900
2100	2600		2900	3200	3500
2400	2300		2600	2900	3100

***All Load Capacities are rated with the mast vertical.

17/25 Versa-Lift with 2 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

2

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Fork Face (mm)	300	7700	8500	9400	10200
	600	6200	6900	7600	8300
	900	5200	5800	6400	6900
	1200	4500	5000	5500	6000
	1500	3900	4400	4800	5200
	1800	3500	3900	4300	4700

Lift Capacities w/Forks & Boom (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	7400	8300	9200	10000
	600	5800	6600	7200	7900
	900	4800	5400	6000	6600
	1200	4100	4600	5100	5600
	1500	3600	4000	4400	4800
	1800	3200	3500	3900	4300
	2100	2900	3200	3500	3900
	2400	2600	2900	3200	3500

Lift Capacities w/Boom Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	7700	8600	9500	10300
	600	6100	6800	7500	8200
	900	5100	5600	6200	6800
	1200	4300	4800	5300	5800
	1500	3700	4200	4600	5000
	1800	3300	3700	4100	4500
	2100	3000	3300	3700	4000
	2400	2700	3000	3300	3600

***All Load Capacities are rated with the mast vertical.

17/25 Versa-Lift with 3 Counterweight Slabs

Slab Weight (kgs)

680

Number of Slabs

3

Standard Wheel Base (mm)

1800

Lift Capacities w/Forks Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Fork Face (mm)	600	3800	9400
900	6800		7600	8300	9100
1200	5700		6300	7000	7600
1500	4900		5400	6000	6600
1800	4300		4800	5300	5800
2100	3800		4300	4700	5100

Lift Capacities w/Forks & Boom (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	8300	9300
600	6600		7400	8200	9000
900	5500		6100	6800	7500
1200	4700		5200	5800	6400
1500	4000		4500	5000	5500
1800	3600		4000	4500	4900
2100	3200		3600	4000	4400
2400	2900		3300	3600	4000

Lift Capacities w/Boom Only (kgs)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	8700	9700
600	6900		7700	8500	9300
900	5700		6400	7000	7700
1200	4800		5400	6000	6600
1500	4200		4700	5200	5700
1800	3700		4200	4600	5100
2100	3300		3700	4100	4500
2400	3000		3400	3800	4100

***All Load Capacities are rated with the mast vertical.