

## 25/35 Versa-Lift with 0 Counterweight Slabs and Sideshifter Carriage

Slab Weight (lbs)

Number of Slabs

Standard Wheel Base (in)

**1900**

**0**

**76**

| <b>Lift Capacities w/Forks Only (lbs)</b> |       |                                       |       |       |       |
|---|-------|---------------------------------------|-------|-------|-------|
|   |       | Counterweight Extension (in)          |       |       |       |
|   |       | 0                                     | 12    | 24    | 36    |
|   |       | Load Center<br>From Fork<br>Face (in) | 24    | 15100 | 17500 |
| 36  | 12200 | 14100                                 | 16100 | 18100 | 18100 |
| 48  | 10200 | 11900                                 | 13500 | 15100 | 15100 |
| 60  | 8800  | 10200                                 | 11600 | 13000 | 13000 |
| 72  | 7700  | 9000                                  | 10200 | 11500 | 11500 |
| 84  | 6900  | 8000                                  | 9100  | 10200 | 10200 |

| <b>Lift Capacities w/Boom Only (lbs)</b> |       |                                       |       |       |       |
|--|-------|---------------------------------------|-------|-------|-------|
|  |       | Counterweight Extension (in)          |       |       |       |
|  |       | 0                                     | 12    | 24    | 36    |
|  |       | Load Center<br>From Boom<br>Face (in) | 12    | 14300 | 16800 |
| 24                                       | 11600 | 13500                                 | 15500 | 17500 | 17500 |
| 36                                       | 9700  | 11400                                 | 13000 | 14600 | 14600 |
| 48                                       | 8400  | 9800                                  | 11200 | 12600 | 12600 |
| 60                                       | 7400  | 8600                                  | 9800  | 11100 | 11100 |
| 72                                       | 6600  | 7700                                  | 8800  | 9900  | 9900  |
| 84                                       | 5900  | 6900                                  | 7900  | 8900  | 8900  |
| 96                                       | 5400  | 6300                                  | 7200  | 8100  | 8100  |

| <b>Lift Capacities w/Forks &amp; Boom (lbs)</b> |      |                                       |       |       |       |
|---|------|---------------------------------------|-------|-------|-------|
|   |      | Counterweight Extension (in)          |       |       |       |
|   |      | 0                                     | 12    | 24    | 36    |
|   |      | Load Center<br>From Boom<br>Face (in) | 24    | 10700 | 12600 |
| 36  | 9000 | 10600                                 | 12200 | 13900 | 13900 |
| 48  | 7700 | 9100                                  | 10500 | 11900 | 11900 |
| 60  | 6800 | 8000                                  | 9300  | 10500 | 10500 |
| 72  | 6000 | 7100                                  | 8200  | 9400  | 9400  |
| 84  | 5400 | 6400                                  | 7400  | 8400  | 8400  |
| 96  | 5000 | 5900                                  | 6800  | 7700  | 7700  |

*\*\*\*All Load Capacities are rated with the mast vertical.*

## 25/35 Versa-Lift with 1 Counterweight Slabs and Sideshifter Carriage

Slab Weight (lbs)

Number of Slabs

Standard Wheel Base (in)

**1900**

**1**

**76**

| <b>Lift Capacities w/Forks Only (lbs)</b>      |    |                              |       |       |       |
|--|----|------------------------------|-------|-------|-------|
|  |    | Counterweight Extension (in) |       |       |       |
|  |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Fork<br/>Face (in)</b> | 24 | 17600                        | 20400 | 23200 | 26100 |
|  | 36 | 14200                        | 16500 | 18800 | 21000 |
|  | 48 | 11900                        | 13800 | 15700 | 17700 |
|  | 60 | 10300                        | 11900 | 13600 | 15200 |
|  | 72 | 9000                         | 10500 | 11900 | 13400 |
|  | 84 | 8000                         | 9300  | 10600 | 11900 |

| <b>Lift Capacities w/Boom Only (lbs)</b>       |    |                              |       |       |       |
|--|----|------------------------------|-------|-------|-------|
|  |    | Counterweight Extension (in) |       |       |       |
|  |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Boom<br/>Face (in)</b> | 12 | 16900                        | 19700 | 22500 | 25300 |
|  | 24 | 13600                        | 15900 | 18200 | 20500 |
|  | 36 | 11400                        | 13300 | 15200 | 17200 |
|  | 48 | 9800                         | 11500 | 13100 | 14800 |
|  | 60 | 8600                         | 10100 | 11500 | 13000 |
|  | 72 | 7700                         | 9000  | 10300 | 11600 |
|  | 84 | 7000                         | 8100  | 9300  | 10400 |
|  | 96 | 6300                         | 7400  | 8400  | 9500  |

| <b>Lift Capacities w/Forks &amp; Boom (lbs)</b> |    |                              |       |       |       |
|---|----|------------------------------|-------|-------|-------|
|   |    | Counterweight Extension (in) |       |       |       |
|   |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Boom<br/>Face (in)</b>  | 24 | 12700                        | 15000 | 17300 | 19500 |
|   | 36 | 10700                        | 12600 | 14500 | 16400 |
|   | 48 | 9200                         | 10800 | 12500 | 14100 |
|   | 60 | 8100                         | 9500  | 10900 | 12400 |
|   | 72 | 7200                         | 8500  | 9800  | 11000 |
|   | 84 | 6500                         | 7600  | 8800  | 10000 |
|   | 96 | 5900                         | 7000  | 8000  | 9100  |

*\*\*\*All Load Capacities are rated with the mast vertical.*

## 25/35 Versa-Lift with 2 Counterweight Slabs and Sideshifter Carriage

Slab Weight (lbs)

Number of Slabs

Standard Wheel Base (in)

**1900**

**2**

**76**

| <b>Lift Capacities w/Forks Only (lbs)</b>      |    |                              |       |       |       |
|--|----|------------------------------|-------|-------|-------|
|  |    | Counterweight Extension (in) |       |       |       |
|  |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Fork<br/>Face (in)</b> | 24 | 20100                        | 23300 | 26500 | 29800 |
|  | 36 | 16300                        | 18900 | 21400 | 24000 |
|  | 48 | 13600                        | 15800 | 18000 | 20200 |
|  | 60 | 11700                        | 13600 | 15500 | 17400 |
|  | 72 | 10300                        | 12000 | 13600 | 15300 |
|  | 84 | 9200                         | 10700 | 12100 | 13600 |

| <b>Lift Capacities w/Boom Only (lbs)</b>       |    |                              |       |       |       |
|--|----|------------------------------|-------|-------|-------|
|  |    | Counterweight Extension (in) |       |       |       |
|  |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Boom<br/>Face (in)</b> | 12 | 19400                        | 22600 | 25800 | 29000 |
|  | 24 | 15700                        | 18300 | 20900 | 23400 |
|  | 36 | 13100                        | 15300 | 17500 | 19700 |
|  | 48 | 11300                        | 13200 | 15100 | 16900 |
|  | 60 | 9900                         | 11600 | 13200 | 14900 |
|  | 72 | 8900                         | 10300 | 11800 | 13300 |
|  | 84 | 8000                         | 9300  | 10600 | 12000 |
|  | 96 | 7300                         | 8500  | 9700  | 10900 |

| <b>Lift Capacities w/Forks &amp; Boom (lbs)</b> |    |                              |       |       |       |
|---|----|------------------------------|-------|-------|-------|
|   |    | Counterweight Extension (in) |       |       |       |
|   |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Boom<br/>Face (in)</b>  | 24 | 14700                        | 17300 | 19900 | 22500 |
|   | 36 | 12400                        | 14500 | 16700 | 18900 |
|   | 48 | 10600                        | 12500 | 14400 | 16300 |
|   | 60 | 9400                         | 11000 | 12600 | 14300 |
|   | 72 | 8300                         | 9800  | 11300 | 12700 |
|   | 84 | 7500                         | 8800  | 10200 | 11500 |
|   | 96 | 6800                         | 8100  | 9300  | 10500 |

*\*\*\*All Load Capacities are rated with the mast vertical.*

## 25/35 Versa-Lift with 3 Counterweight Slabs and Sideshifter Carriage

Slab Weight (lbs)

Number of Slabs

Standard Wheel Base (in)

**1900**

**3**

**76**

| <b>Lift Capacities w/Forks Only (lbs)</b>      |    |                              |       |       |       |
|--|----|------------------------------|-------|-------|-------|
|  |    | Counterweight Extension (in) |       |       |       |
|  |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Fork<br/>Face (in)</b> | 24 | 22600                        | 26200 | 29900 | 33500 |
|  | 36 | 18300                        | 21200 | 24100 | 27000 |
|  | 48 | 15300                        | 17800 | 20200 | 22700 |
|  | 60 | 13200                        | 15300 | 17400 | 19500 |
|  | 72 | 11600                        | 13500 | 15300 | 17200 |
|  | 84 | 10300                        | 12000 | 13600 | 15300 |

| <b>Lift Capacities w/Boom Only (lbs)</b>       |    |                              |       |       |       |
|--|----|------------------------------|-------|-------|-------|
|  |    | Counterweight Extension (in) |       |       |       |
|  |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Boom<br/>Face (in)</b> | 12 | 21900                        | 25500 | 29100 | 32700 |
|  | 24 | 17700                        | 20600 | 23500 | 26400 |
|  | 36 | 14800                        | 17300 | 19700 | 22200 |
|  | 48 | 12800                        | 14900 | 17000 | 19100 |
|  | 60 | 11200                        | 13100 | 14900 | 16800 |
|  | 72 | 10000                        | 11700 | 13300 | 15000 |
|  | 84 | 9000                         | 10500 | 12000 | 13500 |
|  | 96 | 8200                         | 9600  | 10900 | 12300 |

| <b>Lift Capacities w/Forks &amp; Boom (lbs)</b> |    |                              |       |       |       |
|---|----|------------------------------|-------|-------|-------|
|   |    | Counterweight Extension (in) |       |       |       |
|   |    | 0                            | 12    | 24    | 36    |
| <b>Load Center<br/>From Boom<br/>Face (in)</b>  | 24 | 16800                        | 19700 | 22600 | 25500 |
|   | 36 | 14100                        | 16500 | 19000 | 21400 |
|   | 48 | 12100                        | 14200 | 16300 | 18400 |
|   | 60 | 10600                        | 12500 | 14300 | 16200 |
|   | 72 | 9500                         | 11100 | 12800 | 14400 |
|   | 84 | 8600                         | 10000 | 11500 | 13000 |
|   | 96 | 7800                         | 9100  | 10500 | 11900 |

\*\*\*All Load Capacities are rated with the mast vertical.