

25/35 Versa-Lift with 0 Counterweight Slabs

Slab Weight (kg)
860

Number of Slabs
0

Standard Wheel Base (mm)
1900

Lift Capacities w/Forks Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Fork Face (mm)	600	7700	8900	10100	11300
	900	6100	7100	8100	9000
	1200	5100	5900	6700	7500
	1500	4400	5100	5700	6400
	1800	3800	4400	5000	5600
	2100	3400	3900	4500	5000

Lift Capacities w/Boom Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	7300	8500	9700	11000
	600	5800	6800	7800	8700
	900	4900	5700	6500	7300
	1200	4200	4900	5500	6200
	1500	3600	4200	4800	5400
	1800	3200	3800	4300	4800
	2100	2900	3400	3900	4400
	2400	2600	3100	3500	4000

Lift Capacities w/Forks & Boom (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	600	5400	6400	7300	8300
	900	4500	5300	6100	6900
	1200	3800	4500	5200	5900
	1500	3400	4000	4600	5200
	1800	3000	3500	4100	4600
	2100	2700	3200	3700	4100
	2400	2400	2900	3300	3800

***All Load Capacities are rated with the mast vertical.

25/35 Versa-Lift with 1 Counterweight Slabs

Slab Weight (kg)
860

Number of Slabs
1

Standard Wheel Base (mm)
1900

Lift Capacities w/Forks Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Fork Face (mm)	600	8900	10300
900	7100		8200	9300	10500
1200	5900		6800	7800	8700
1500	5100		5900	6600	7400
1800	4400		5100	5800	6500
2100	3900		4500	5200	5800

Lift Capacities w/Boom Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	8500	9900
600	6800		7900	9000	10200
900	5700		6600	7500	8500
1200	4900		5600	6400	7200
1500	4200		4900	5600	6300
1800	3800		4400	5000	5600
2100	3400		3900	4500	5100
2400	3100		3600	4100	4600

Lift Capacities w/Forks & Boom (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	600	6400	7500
900	5300		6200	7200	8100
1200	4500		5300	6100	6900
1500	4000		4700	5400	6100
1800	3500		4100	4800	5400
2100	3200		3700	4300	4800
2400	2900		3400	3900	4400

***All Load Capacities are rated with the mast vertical.

25/35 Versa-Lift with 2 Counterweight Slabs

Slab Weight (kg)
860

Number of Slabs
2

Standard Wheel Base (mm)
1900

Lift Capacities w/Forks Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Fork Face (mm)	600	10100	11700	13300	14900
	900	8100	9300	10600	11900
	1200	6700	7800	8800	9900
	1500	5700	6600	7600	8500
	1800	5000	5800	6600	7400
	2100	4500	5200	5900	6600

Lift Capacities w/Boom Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	300	9700	11300	12900	14500
	600	7800	9000	10300	11600
	900	6500	7500	8600	9600
	1200	5500	6400	7400	8300
	1500	4800	5600	6400	7200
	1800	4300	5000	5700	6400
	2100	3900	4500	5100	5800
	2400	3500	4100	4700	5200

Lift Capacities w/Forks & Boom (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
Load Center From Boom Face (mm)	600	7300	8600	9900	11200
	900	6100	7200	8200	9300
	1200	5200	6100	7000	7900
	1500	4600	5400	6200	6900
	1800	4100	4800	5500	6200
	2100	3700	4300	4900	5600
	2400	3300	3900	4500	5000

***All Load Capacities are rated with the mast vertical.

25/35 Versa-Lift with 3 Counterweight Slabs

Slab Weight (kg)
860

Number of Slabs
3

Standard Wheel Base (mm)
1900

Lift Capacities w/Forks Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Fork Face (mm)	600	11300	13100
900	9000		10500	11900	13300
1200	7500		8700	9900	11100
1500	6400		7400	8500	9500
1800	5600		6500	7400	8300
2100	5000		5800	6600	7400

Lift Capacities w/Boom Only (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	300	11000	12700
600	8700		10200	11600	13000
900	7300		8500	9600	10800
1200	6200		7200	8300	9300
1500	5400		6300	7200	8100
1800	4800		5600	6400	7200
2100	4400		5100	5800	6500
2400	4000		4600	5200	5900

Lift Capacities w/Forks & Boom (kg)					
		Counterweight Extension (mm)			
		0	300	600	900
		Load Center From Boom Face (mm)	600	8300	9700
900	6900		8100	9300	10500
1200	5900		6900	7900	9000
1500	5200		6100	7000	7800
1800	4600		5400	6200	7000
2100	4100		4800	5600	6300
2400	3800		4400	5000	5700

***All Load Capacities are rated with the mast vertical.